

| | |
|-----------------------|---------------------------------|
| SPECIFICATIONS | 2000 SALEEN Explorer XP8 |
|-----------------------|---------------------------------|

| | |
|--------------------------|-----------|
| GENERAL | |
| Curb Weight, lb. | 3800-4450 |
| Weight Distribution, F/R | |
| Fuel Capacity, gal. | 21 |
| Wheelbase, in. | 111.6 |
| Track, F/R | |
| Width | 70.2 |
| Length | 191 |
| Height | 65.5 |
| Trunk Space, cubic ft. | |

| | |
|----------------------|---|
| ENGINE | |
| Type | V8 |
| Bore and Stroke | |
| Displacement | 5.0 L, 302 c.i.d. |
| Compression Ratio | 8.5:1 |
| Induction System | |
| Camshaft | |
| Pistons | |
| Exhaust System | Saleen 2.5 in. stainless steel 4-way catalytic high flow exhaust and muffler system |
| Horsepower | 222 hp @ 4200 RPM |
| Torque | 298 ft.-lbs. @ 3300 RPM |
| Fuel | Premium Unleaded 92 Octane |
| Supercharger, Saleen | Optional |
| Horsepower | 286 hp @ 4200 RPM |
| Torque | 333 ft.-lbs. @ 3000 RPM |

| | |
|-------------------|--------------------------------|
| DRIVETRAIN | |
| Transmission | 4 Speed Automatic Transmission |

| | |
|-------------------|---|
| SUSPENSION | |
| Front | Independent SLA, torsion bar, high pressure Saleen/Racecraft N2 gas shock absorbers and Saleen/Racecraft front sway bar and pivot bushings |
| Rear | Semi-floating type rear axle, variable rate leaf spring, high pressure Saleen/Racecraft N2 gas shock absorbers and Saleen/Racecraft sway bar and pivot bushings |

| | |
|--|---------------------|
| BRAKES | |
| Power 4-wheel ABS Brakes | |
| 11.3 in. Dual Piston Vented Disc (Front) | Standard |
| 11.2 in. Disc (Rear) | Standard |
| 13 in. rotors with 4-piston front calipers | Optional (AWD only) |

| | |
|-------------------------|----------|
| WHEELS AND TIRES | |
| Saleen Aluminum Wheels | |
| 18 in. x 8.5 in. Front | Standard |
| 18 in. x 8.5 in. Rear | Standard |
| Chrome alloy wheels | Optional |
| Pirelli Scorpion Zeros | |
| P255/55 R-18 (Front) | Standard |
| P255/55 R-18 (Rear) | Standard |