

<b>SPECIFICATIONS</b>		<b>2000 SALEEN S281</b>	
<b>GENERAL</b>	<b>Coupe</b>	<b>Convertible</b>	
Curb Weight, lb.	3064+ Saleen	3203+ Saleen	
Weight Distribution, F/R	56/44	58/42	
Fuel Capacity, gal.	15.7		
Wheelbase, in.	101.3		
Track, F/R	59.7/61.5		
Width	73.1		
Length	183.2		
Height	53.1	53.2	
Trunk Space, cubic ft.	10.9	7.7	

### **ENGINE**

Type	4.6L, 2V, SOHC V8		
Bore and Stroke	3.60 x 3.60 in.		
Displacement	4.6L, 281c.i.d		
Accessory Pulleys	Saleen High Performance Pulleys		
Exhaust System	Saleen Stainless 2.5 in. High Flow Custom Exhaust		
Horsepower	285 hp @ 5100 RPM		
Torque	315 ft.-lbs. @ 4100 RPM		
Fuel	Premium Unleaded 92-Octane		
Saleen Intercooled Supercharger (Optional)	Saleen Roots Style Supercharger, Water-to-Water Intercooler, Calibrated Saleen Engine Management System, Saleen Cast 356-T6 Aluminum Manifold, 24lb./hr fuel Injectors		
Horsepower	350 hp @ 5000 RPM		
Torque	410 ft.-lb. @ 3000 RPM		

### **DRIVETRAIN**

Transmission	Saleen Quick Ratio 5 Speed Transmission	(3.08
	DIFE on Supercharger Model)	
8.8 in. Differential 3.27 Ratio	Standard	
8.8 in. Differential 3.55 Ratio	Optional	
Saleen Posi-Traction	Optional	

### **SUSPENSION**

Front	Hybrid Macpherson strut with Saleen Racecraft struts and variable rate springs mounted on lower control arms. 1.38 in. stabilizer bar with urethane pivot bushing. Specially calibrated suspension settings
Rear	Live axle four bar link with variable rate coil-springs on lower trailing arms, stabilizer bar, Quadra Shock System with Saleen Racecraft shocks

### **BRAKES**

Power 4-Wheel ABS Brakes	
10.8 in. Dual Piston Vented Disc (Front)	Standard
10.5 in. Disc (Rear)	
Saleen ABS 4-Piston Calipers	
13.0 in. Grooved Disc (Front)	Optional

### **WHEELS AND TIRES**

Saleen Five Spoke Alloy Wheels	
18 in. x 9 in. Front	Standard
18 in. x 9 in. Rear	Standard
18 in. x 10 in. Rear	Optional
High Performance Pirelli P7000	
P255/35 ZR-18 (Front)	Standard
P265/35 ZR-18 (Rear)	Standard
High Performance Pirelli P-Zero Upgrade	
P265/35 ZR-18 (Front)	Optional
P295/35 ZR-18 (Rear)	Optional