



| <b>SPECIFICATIONS</b>    |              | <b>2003 SALEEN S281</b> |  |
|--------------------------|--------------|-------------------------|--|
| <b>GENERAL</b>           | <b>Coupe</b> | <b>Convertible</b>      |  |
| Curb Weight, lb.         | 3428         | 3620                    |  |
| Weight Distribution, F/R | 57/43        | 57/43                   |  |
| Fuel Capacity, gal.      | 15.7         |                         |  |
| Wheelbase, in.           | 101.3        |                         |  |
| Track, F/R               | 59.7/61.5    |                         |  |
| Width                    | 73.1         |                         |  |
| Length                   | 185.2        |                         |  |
| Height                   | 52           | 52.2                    |  |
| Trunk Space, cubic ft.   | 10.8         | 7.7                     |  |

### **ENGINE**

|                   |  |  |  |
|-------------------|--|--|--|
| Type              | 4.6L, 2V, SOHC V-8                       |  |  |
| Bore and Stroke   | 3.60 x 3.60 in.                          |  |  |
| Displacement      | 4.6L, 281C.I.                            |  |  |
| Accessory Pulleys | Saleen Underdrive Pulleys                |  |  |
| Exhaust System    | Saleen Stainless, 2.5" Exhaust w/ X-Pipe |  |  |
| Horsepower        | 290 hp @ 5100 RPM                        |  |  |
| Torque            | 330 ft.-lbs. @ 4100 RPM                  |  |  |
| Fuel              | Premium Unleaded 91 Octane               |  |  |

### **DRIVETRAIN**

|                                 |   |  |  |
|---------------------------------|---|--|--|
| Transmission                    | Saleen Quick Ratio 5-Speed Transmission |  |  |
| 8.8 in. Differential 3.27 Ratio | Standard                                |  |  |
| 8.8 in. Differential 3.55 Ratio | Optional                                |  |  |
| Saleen MaxGrip                  | Optional                                |  |  |

### **SUSPENSION**

|       |  |  |  |
|-------|--|--|--|
| Front | variable rate springs mounted on lower control arms, 1.38 in. stabilizer bar with urethane pivot bushings, specially calibrated suspension settings. |  |  |
| Rear  | stabilizer bar, Quadra Shock System with Saleen Racecraft shocks   |  |  |

### **BRAKES**

|  |          |  |  |
|--|----------|--|--|
| Power 4-Wheel ABS Brakes                 |          |  |  |
| 10.8 in. Dual Piston Vented Disc (Front) | Standard |  |  |
| 10.5 in. Disc (Rear)                     |          |  |  |
| Saleen ABS 4-Piston Calipers             |          |  |  |
| 13.0 in. Grooved Disc (Front)            | Optional |  |  |

### **WHEELS AND TIRES**

|   |          |  |  |
|---|----------|--|--|
| Saleen Five Spoke Alloy Wheels                |          |  |  |
| 18 in. x 9 in. Front                          | Standard |  |  |
| 18 in. x 9 in. Rear                           | Standard |  |  |
| 18 in. x 10 in. Rear                          | Optional |  |  |
| High Performance Pirelli P7000                |          |  |  |
| P255/35ZR18 (Front)                           | Standard |  |  |
| P265/35ZR18 (Rear)                            | Standard |  |  |
| High Performance Pirelli P-Zero Rosso Upgrade |          |  |  |
| P265/35ZR18 (Front)                           | Optional |  |  |
| P295/35ZR18 (Rear)                            | Optional |  |  |