



SPECIFICATIONS		2003 SALEEN S281E	
GENERAL	Coupe	Convertible	
Curb Weight, lb.	3428	3620	
Weight Distribution, F/R	57/43	57/43	
Fuel Capacity, gal.	15.7		
Wheelbase, in.	101.3		
Track, F/R	59.7/61.5		
Width	73.1		
Length	185.2		
Height	52	52.2	
Trunk Space, cubic ft.	10.8	7.7	

ENGINE

Type	4.6L, 2V, SOHC V-8		
Bore and Stroke	3.60 x 3.60 in.		
Displacement	4.6L, 281C.I.		
Crankshaft	Special Saleen Forged Steel		
Connecting Rods	Saleen Forged Steel		
Pistons	Saleen Forged Aluminum		
Cylinder Heads	Saleen Aluminum with Saleen Camshaft and Super Duty Valve Springs		
Exhaust System	Saleen Stainless, 2.5" Center Outlet Exhaust w/ X-Pipe		
Horsepower	445 hp @ 6,000 RPM		
Torque	450 ft.-lbs. @ 4000 RPM		
Fuel	Premium Unleaded 91 Octane		
Saleen Intercooled Supercharger	Saleen Series V "Screw-Type" Supercharger, Saleen Water-to-Air Intercooler, Saleen "PowerFlash" Performance Calibration System, Saleen 90 mm Mass Air Sensor, 42lb./hr Fuel Injectors		

DRIVETRAIN

Transmission	Saleen Quick Ratio 6-Speed Transmission		
8.8 in. Differential 3.55 Ratio	Standard		
Exclusive Saleen "Max Grip" Differential	Standard		

SUSPENSION

Front	Hybrid Macpherson strut with Saleen Racecraft system including N2 struts, variable rate springs mounted on lower control arms. 1.38" stabilizer bar with urethane pivot bushing. Specially calibrated suspension settings		
Rear	Live axle four bar link with Saleen Racecraft variable rate coil-spings on boxed lower trailing arms, 0.94" stabilizer bar, Quadra Shock System with Saleen N2 Racecraft shocks.		

BRAKES

Power 4-Wheel ABS Brakes			
Saleen Premium, 14.0 in. 2-Piece Slotted Disc (Front)	Standard		
10.5 in. Disc (Rear)	Standard		
Saleen ABS 4-Piston Calipers (front)	Standard		

WHEELS AND TIRES

Saleen Five Spoke Alloy Wheels			
18 in. x 9 in. Front	Standard		
18 in. x 10 in. Rear	Standard		
Chrome Finish	Optional		
High Performance Pirelli P-Zero Rosso			
P265/35ZR18 (Front)	Standard		
P295/35ZR18 (Rear)	Standard		