



SPECIFICATIONS		2003 SALEEN S281SC	
GENERAL	Coupe	Convertible	
Curb Weight, lb.	3428	3620	
Weight Distribution, F/R	57/43	57/43	
Fuel Capacity, gal.	15.7		
Wheelbase, in.	101.3		
Track, F/R	59.7/61.5		
Width	73.1		
Length	185.2		
Height	52	52.2	
Trunk Space, cubic ft.	10.8	7.7	

ENGINE

Type	4.6L, 2V, SOHC V-8		
Bore and Stroke	3.60 x 3.60 in.		
Displacement	4.6L, 281C.I.		
Exhaust System	Saleen Stainless, 2.5" Exhaust w/ X-Pipe		
Horsepower	375 hp @ 5800 RPM		
Torque	415 ft.-lb. @ 3500 RPM		
Fuel	Premium Unleaded 91 Octane		
Saleen Intercooled Supercharger	Saleen Series IV Twin Screw Supercharger, 4 inch power tube, 80mm Cast 356-T6 Aluminum Inlet Tube, Saleen Cast 356-T6 Aluminum Manifold, Water-to-Air Intercooler, Calibrated Saleen Engine Management System, 30lb./hr Fuel		

DRIVETRAIN

Transmission	Saleen Quick Ratio 5-Speed Transmission		
8.8 in. Differential 3.27 Ratio	Standard		
Saleen MaxGrip	Optional		

SUSPENSION

Front	Hybrid Macpherson struts with Saleen Racecraft system including N2 struts, variable rate springs mounted on lower control arms, 1.38 in. stabilizer bar with urethane pivot bushings, specially calibrated suspension settings.		
Rear	Live axle four bar link with variable rate coil-springs on lower trailing arms, stabilizer bar, Quadra Shock System with Saleen Racecraft shocks		

BRAKES

Power 4-Wheel ABS Brakes			
10.8 in. Dual Piston Vented Disc (Front)	Standard		
10.5 in. Disc (Rear)			
Saleen ABS 4-Piston Calipers			
13.0 in. Grooved Disc (Front)	Optional		

WHEELS AND TIRES

Saleen Five Spoke Alloy Wheels			
18 in. x 9 in. Front	Standard		
18 in. x 9 in. Rear	Standard		
18 in. x 10 in. Rear	Optional		
High Performance Pirelli P7000			
P255/35ZR18 (Front)	Standard		
P265/35ZR18 (Rear)	Standard		
High Performance Pirelli P-Zero Rosso Upgrade			
P265/35ZR18 (Front)	Optional		
P295/35ZR18 (Rear)	Optional		