



<b>SPECIFICATIONS</b>		<b>2004 SALEEN S281E</b>	
<b>GENERAL</b>	<b>Coupe</b>	<b>Convertible</b>	
Curb Weight, lb.	3428	3620	
Weight Distribution, F/R	57/43	57/43	
Fuel Capacity, gal.	15.7		
Wheelbase, in.	101.3		
Track, F/R	59.7/61.5		
Width	73.1		
Length	185.2		
Height	52.0	52.2	
Trunk Space, cubic ft.	10.8	7.7	

### **ENGINE**

Type	4.6L, 2V, SOHC V-8		
Bore and Stroke	3.60 x 3.60 in.		
Displacement	4.6L, 281C.I.		
Crankshaft	Special Saleen Forged Steel		
Connecting Rods	Saleen Forged Steel		
Pistons	Saleen Forged Aluminum		
Cylinder Heads	Saleen Aluminum with Saleen Camshaft and Super Duty Valve Springs		
Exhaust System	Saleen Stainless, 2.5" Center Outlet Exhaust		
Horsepower	445 hp @ 6,000 RPM		
Torque	450 ft.-lbs. @ 4000 RPM		
Fuel	Premium Unleaded 91 Octane		
Saleen Intercooled Supercharger	Saleen Series V "Screw-Type" Supercharger, Saleen Water-to-Air Intercooler, Saleen PowerFlash Engine Management, Saleen 90 mm Mass Airflow Sensor, 42lb./hr Fuel Injectors		

### **DRIVETRAIN**

Transmission	Saleen Quick Ratio 6-Speed Transmission		
8.8 in. Differential 3.55 Ratio	Standard		
Exclusive Saleen "Max Grip" Differential	Standard		

### **SUSPENSION**

Front	Hybrid Macpherson with Saleen Racecraft system including N2 struts, variable-rate coil springs mounted on lower control arms. 1.38-in. stabilizer (anti-roll) bar with urethane pivot bushings. Specially calibrated suspension settings		
Rear	Live axle four bar link with variable-rate coil springs on lower trailing arms, Quadra Shock System with Saleen Racecraft shocks; stabilizer (anti-roll) bar		

### **BRAKES**

Power 4-Wheel ABS Brakes			
Saleen Premium 4-Piston Calipers with 14.0 in 2-Piece Slotted and Vented Disc (Front)	Standard		
10.5 in. Disc (Rear)	Standard		

### **WHEELS AND TIRES**

Saleen Five Spoke Alloy Wheels			
18 in. x 9 in. Front	Standard		
18 in. x 10 in. Rear	Standard		
Chrome Finish	Optional		
High Performance Pirelli P-Zero Rosso			
P265/35ZR18 (Front)	Standard		
P295/35ZR18 (Rear)	Standard		