



S A L E E N S 7



**SALEEN**



# S A L E E N S 7



**GENERAL**  
 Curb Weight - 2750 Pounds (1247 kg)  
 Weight Distribution - F/R 40/60%  
 Fuel Capacity - 19 US Gal (72 liters)  
 Wheelbase - 106.25 in (2700 mm)  
 Track F/R - 68.75 in (1748 mm)/67.25 in (1710 mm)  
 Width - 73.3 in (1862 mm)  
 Front Overhang - 40.8 in (1031 mm)  
 Rear Overhang - 41.1 in (1045 mm)  
 Length - 188 in (4774 mm)  
 Height - 41 inches (1041 mm)  
 Ground Clearance - 4 inches (100 mm)  
 Trunk Space F/R - 2.65 cu ft (75 liter)/2.82 cu ft (80 liter)

**CHASSIS**  
 Space frame 4130 lightweight steel with honeycomb composite panels

**ENGINE**  
 Type - All-Aluminum V-8 2 v cam-in-block  
 Displacement - 7 liter  
 Bore and Stroke - 4.120 x 4 in (104.8 x 101.8 mm)  
 Pistons - Forged  
 Connecting Rods - 4340 forged steel  
 Crankshaft - 4340 forged steel  
 Induction System - Roof intake feeding single 90 mm mass air meter feeding carbon fiber plenum, Twin Ball-Bearing Turbo, Oval bore Throttle body  
 Heads - CNC machined all-aluminum Saleen high flow  
 Valves - Stainless steel heads with titanium retainers  
 Intake - 2.125 in (54 mm)  
 Exhaust - 1.625 in (41.3 mm)  
 Beryllium exhaust seats  
 Valve Train - Solid lifter  
 Exhaust System - Stainless steel high flow with merge collector incorporating dual catalysts per cylinder bank and EGR system, Twin 44mm wastegates  
 Required Fuel - 91 octane  
 Alternator - 140 amps  
 Battery - 12 volts  
 Drive (FEAD) - Compact drive system with side-mounted water pump  
 Emission Control System - OBO-II compliant, dual heated oxygen sensor per bank, high-volume EVAP system

**ENGINE** (continued)  
 Fuel System - High capacity returnless with 43 lb./hr injectors with Dual Pumps  
 Oil System - High Vacuum dry sump configuration 12.6 qt. [12 liter] aluminum oil tank  
 Horsepower - 750 hp @ 6300 rpm  
 Torque - 700 ft lbs. @ 4800 rpm  
 Redline - 6500 rpm

**COOLING SYSTEM**  
 Carbon fiber front intake feeding twin front-mounted aluminum water radiators with WCU controlled electric cooling fans. Side-mounted oil-air coolers.

**ELECTRONICS**  
 Saleen PowerFlash control system computer integrated coil-on plug ignition system

**DRIVETRAIN**  
 Transmission: Longitudinal, 6-speed all synchro-mesh transaxle  
 Transmission Ratios: 1st -2.860, 2nd-1.610, 3rd-1.140, 4th-0.958, 5th-0.807, 6th-0.642, Final Drive Ratio: 3.7  
 Limited slip differential  
 Lightweight inboard and outboard tri-rod joints. High torque capacity steel halfshafts  
 Clutch: 8.0 in (203.2mm) metallic, hybrid 2-plate, hydraulic actuation

**SUSPENSION**  
 Front Suspension System: Unequal length, double wishbones, lightweight aluminum dampers with dual stage coilover springs. Front anti-roll bar CNC-machined billet aluminum flow through uprights  
 Rear Suspension System: Unequal length, double wishbones, lightweight aluminum dampers with dual stage coilover springs, CNC-machined billet aluminum flow through uprights

**BRAKES**  
 Saleen engineered/Brembo supplied lightweight aluminum, six-piston calipers front/rear  
 15 in. Ventilated Disc (Front) / 14 in. Ventilated Disc (Rear)  
 Lightweight aluminum disc mounting belts

**WHEELS & TIRES**  
 Saleen Forged alloy wheels  
 Center locking wheel nuts with automatic safety locks: 19 in x 9.5 in. Front wheels, 20 in x 12 in. Rear wheels  
 High Performance Michelin Pilot Sport tires  
 Front: 275/30-19 / Rear: 345/25-20

**SAFETY FEATURES**  
 Integrated roll protection  
 Aluminum honeycomb impact absorbing panels  
 3-point seat belts with automatic seat belt tensioners  
 Carbon fiber rocker panels and doors  
 Aluminum honeycomb front crush structure, integrated rear crumple zones  
 Center position fuel tank, passenger side filler

**INTERIOR FEATURES**  
 Interior Colors:  
 Tan Multi-Tone Leather/Suede  
 Black Multi-Tone Leather/Suede  
 Seating and Trim:  
 Aluminum and body color accents  
 Performance sports seating  
 Custom fitted driver seating position  
 Leather wrapped steering wheel  
 Rear-view video camera with interior LCD display  
 240 mph speedometer  
 Central-mounted tachometer  
 Comfort and Convenience:  
 High volume flow-through ventilation system  
 Air conditioning

**EXTERIOR FEATURES**  
 Dual power-operated door mirrors  
 Projector beam headlights  
 Heat rejecting tinted glass  
 Autoclave carbon fiber body panels  
 Advanced wind tunnel developed aerodynamics, including integrated spitchannel air flow throughout car; full underside aerodynamics; advanced design front tray & side skirts; integrated full body wing  
 Fully adjustable tilt & telescoping steering column  
 Power windows  
 Power door locks with central locking system  
 Variable intermittent windshield wipers  
 Electric heated front windshield  
 Custom-made fitted luggage  
 Custom car cover  
 Remote open doors and trunk

**OPTIONS**  
 Polished wheels  
 GPS Navigation System



**Exterior Colors:**  
 Speedlab Yellow  
 Saleen S7 Silver  
 Saleen S7 Black  
 Lizstick Red  
 Pearl White  
 Black Metallic  
 Victory Blue  
 Bright Signature Red  
 Beryllium



## SALEEN®

POWER IN THE HANDS OF A FEW

Specifications and prices subject to change without notice.

All product illustrations and specifications are based upon current information at the time of publications. Saleen, Inc., reserves the right to mark changes from time to time, without notice or obligation, in prices, specifications, colors and materials, and to change or discontinue models or optional equipment. Saleen, Inc., does not encourage or condone unsafe or illegal driving. Always wear your seat belt.

©Saleen, 2006. "Saleen," S7, Racecraft, PowerFlash, Power in the Hands of a Few and other marks are registered trademarks of Saleen, Inc.

© Saleen Owners and Enthusiasts Club • www.soec.org • Reprinted with permission of Saleen, Inc. • Reproductions require further permission.

Irvine, California 949 597 4900

www.saleen.com