

ACCUFAB

Congratulations on your purchase of the original and finest clutch cable kit in the business. Special features are as follows:

- Billet aluminum quadrant
- Increased ratio
- 4130 chrome moly adjustable rod end and spherical nut.
- All components made in the USA.

Clutch Cable Removal

1. Lift clutch pedal to its upward most position to disengage pawl and quadrant. Push quadrant forward and unhook cable from quadrant and allow it to swing rearward.
2. From engine side, remove screw that holds cable assembly to firewall. Pull cable through into engine compartment. Remove cable bracket screw from fender apron.
3. Raise vehicle on a hoist or car stand. Only work on vehicle properly supported. Remove clutch cable dust cover from bellhousing and remove clip retainer holding cable assembly to bellhousing. Slide ball on end of cable through clutch fork and remove cable.

Self Adjusting Assembly Removal


1. Remove hairpin clips from both quadrant and pawl. Save clips.
2. Remove quadrant and large spring.
3. Remove pawl spring using a hook tool and remove pawl.

Note: *Quadrant, pawl and both springs will no longer be used.*

Quadrant and Cable Installation

1. Install aluminum quadrant and secure with hairpin clips.
2. Route cable through engine compartment and lower vehicle. Attach cable bracket to fender apron and push cable assembly into hole in firewall. Secure insulator with screw.
3. From inside, hook cable end over rear of quadrant.
4. From under car, insert cable through bellhousing and insert cable through clutch fork. Install clip retainer that holds cable into bellhousing.
5. Install spherical nut with radius toward clutch fork. Install jam nut behind spherical nut. Do not secure. Remove all free play from cable.
6. Press in clutch a few times to the floor and check free play again under the car.
7. Check adjustment by:
 - a. Start car and place in first gear.
 - b. Lift clutch pedal and engine should load when pedal is approximately half way up.
8. Tighten locknut and install dust cover.

Note:
If you have any problems, call our tech line at (909) 930-9852.



Thank you for your purchase.